



**HICKORY SPRINGS®**

A DIVISION OF HSM

For additional information visit:  
[www.hickorysprings.com](http://www.hickorysprings.com)

## Platinum Plus Mattress



|                            |                                                                                                                                                                 |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b><u>SPRING</u></b>       | 253 3 ¾ 13 ½ GAUGE BONNELL UNIT. HEAT TEMPERED FOR STRENGTH AND DURABILITY.                                                                                     |
| <b><u>INSULATORS</u></b>   | A DENSIFIED .75oz FIBER INSULATOR THAT IS STAPLED TO THE TOP AND THE BOTTOM OF THE SPRING UNIT.                                                                 |
| <b><u>QUILTING</u></b>     | A 1 OZ LAYER OF LOW MELT FIBER IS MULTI-NEEDLE QUILTED TO DAMASK TICKING FOR COMFORT. A .5 OZ POLYESTER FIBER IS QUILTED IN THE MATCHING BORDER.                |
| <b><u>FABRIC</u></b>       | 52% POLYESTER, 48% POLYPROPYLENE PLATINUM DAMASK TICKING                                                                                                        |
| <b><u>BOTTOM</u></b>       | 14 GAUGE COLOR COORDINATED STITCH BOND FILLER PANEL                                                                                                             |
| <b><u>BINDING TAPE</u></b> | A 1 ¼" POLYESTER BINDING TAPE IS SEWN TO TOP AND BOTTOM OF MATTRESS.                                                                                            |
| <b><u>CONSTRUCTION</u></b> | THE INSULATORS ARE STAPLED ON THE SPRING UNIT. THE DAMASK COVER IS THEN PLACED OVER THE SPRING UNIT. A MATCHING TOP IS THEN TAPED EDGED WITH 1 ¼" BINDING TAPE. |
| <b><u>COIL COUNT</u></b>   | QUEEN 299, FULL 253                                                                                                                                             |
| <b><u>PACKAGING</u></b>    | THE FINISHED MATTRESS IS PLACED IN A SEALED 2 MIL PLASTIC TO PREVENT SOILING.                                                                                   |

**MEETS 16 CFR 1632 AND 16 CFR 1633.**



### **FOR PRODUCT INFORMATION & SALES**

#### **HICKORY SPRINGS**

235 2ND Avenue NW | PO Box 128 • Hickory NC 28603-0128 | Telephone 828-328-2201

#### **Blue Ridge Products**

3050 Main Avenue NW | Hickory NC 28601 | Telephone 828-322-7990