

Platinum Fiber HM Sofa Mattress



SPRING 253 3 ¾ 13 ½ GAUGE BONNELL UNIT. HEAT

TEMPERED FOR STRENGTH AND

DURABILITY.

INSULATORS A .75 OZ POLYESTER INSULATOR IS

STAPLED TO THE TOP AND BOTTOM OF

THE SPRING.

QUILTING A 1 OZ LAYER OF LOW MELT FIBER IS

MULTI-NEEDLE QUILTED TO DAMASK TICKING FOR COMFORT. A .75 OZ POLYESTER FIBER IS QUILTED IN THE

MATCHING BORDER.

FABRIC 45% POLYESTER, 55% POLYPROPYLENE

DAMASK — PLATINUM

BOTTOM 14 GAUGE COLOR COORDINATED STITCH

BOND FILLER PANEL

BINDING TAPE A 1 1/4" POLYESTER BINDING TAPE IS SEWN

TO TOP AND BOTTOM OF MATTRESS.

CONSTRUCTION THE INSULATORS ARE STAPLED ON SPRING

UNIT. THE DAMASK COVER IS THEN PLACED OVER THE SPRING UNIT. A MATCHING TOP IS THEN TAPED EDGED WITH 1 1/4" BINDING

TAPE.

COIL COUNT QUEEN 299, FULL 253

PACKAGING THE FINISHED MATTRESS IS PLACED IN A

SEALED 2 MIL PLASTIC TO PREVENT

SOILING.

MEETS 16 CFR 1632 AND 16 CFR 1633.



FOR PRODUCT INFORMATION & SALES

Hickory Springs Manufacturing

235 2ND Avenue NW | PO Box 128 • Hickory NC 28603-0128 | Telephone 828-328-2201

Blue Ridge Products

3050 Main Avenue NW | Hickory NC 28601 | Telephone 828-322-7990