



HICKORY SPRINGS[®]
MANUFACTURING COMPANY

For additional information visit:
www.hickorysprings.com

6" Hospitality Foam Sofa Mattress



<u>SPRING</u>	312 3/4 13 1/2 GAUGE BONNELL UNIT. HEAT TEMPERED FOR STRENGTH AND DURABILITY.
<u>INSULATORS</u>	ONE .75 OZ PER SQUARE FOOT FIBER PAD IS STAPLED TO THE TOP, AND ONE .75 OZ PAD IS STAPLED TO THE BOTTOM SIDE OF THE SPRING UNIT.
<u>QUILTING</u>	A 3/8" POLYURETHANE FOAM TOPPER AND A .50 OZ RAYON/POLYESTER FLAME RETARDANT BARRIER IS MULTI NEEDLE QUILTED TO DAMASK TICKING FOR COMFORT.
<u>TOPPER</u>	A 5/8" POLYURETHANE FOAM TOPPER FOR ADDITIONAL COMFORT.
<u>TUFT</u>	MATTRESS IS LACE TUFTED WITH A BRAIDED NYLON.
<u>FABRIC</u>	45% POLYESTER, 55% POLYPROPYLENE DAMASK – FRENCH BLUE
<u>BOTTOM</u>	14 GAUGE COLOR COORDINATED STITCH BOND FILLER PANEL
<u>BINDING TAPE</u>	A 1 1/4" POLYESTER BINDING TAPE IS SEWN TO TOP AND BOTTOM OF MATTRESS.
<u>CONSTRUCTION</u>	THE INSULATORS ARE STAPLED ON SPRING UNIT. A 5/8" POLYURETHANE FOAM TOPPER IS STAPLED TO THE INSULATOR. THE DAMASK COVER IS THEN PLACED OVER THE SPRING UNIT. A MATCHING TOP IS THEN TAPED EDGED WITH 1 1/4" BINDING TAPE.
<u>LABEL</u>	SEWN LABEL
<u>COIL COUNT</u>	QUEEN 345, FULL 299
<u>PACKAGING</u>	THE FINISHED MATTRESS IS PLACED IN A SEALED 2 MIL PLASTIC TO PREVENT SOILING.

MEETS 16 CFR 1632 AND 16 CFR 1633.

FOR PRODUCT INFORMATION & SALES

Hickory Springs Manufacturing

235 2ND Avenue NW | PO Box 128 • Hickory NC 28603-0128 | Telephone 828-328-2201

Blue Ridge Products

3050 Main Avenue NW | Hickory NC 28601 | Telephone 828-322-7990