



## 6" Hospitality Hybrid Sofa Mattress





**SPRING** 312 3 ¾ 13 ½ GAUGE BONNELL UNIT. HEAT

TEMPERED FOR STRENGTH AND DURABILITY.

**INSULATORS** A .75 OZ POLYESTER INSULATOR IS STAPLED

TO THE TOP AND BOTTOM.

**QUILTING** A 1 OZ LAYER OF LOW MELT FIBER IS MULTI-

NEEDLE QUILTED TO DAMASK TICKING FOR COMFORT. A .75 OZ POLYESTER FIBER IS QUILTED IN THE MATCHING BORDER.

**TOPPER** 1.25 OZ VISCO GEL TOPPER FOR ADDITIONAL

COMFORT

**FABRIC** 45% POLYESTER, 55% POLYPROPYLENE

**DAMASK - WHITE** 

**BOTTOM** 14 GAUGE COLOR COORDINATED STITCH

**BOND FILLER PANEL** 

**BINDING TAPE** A 1 1/4" POLYESTER BINDING TAPE IS SEWN TO

TOP AND BOTTOM OF MATTRESS.

**CONSTRUCTION** THE INSULATORS PADS ARE STAPLED ON

TOP AND BOTTOM OF SPRING UNIT. THE 1.25 OZ VISCO GEL PAD IS APPLIED ON TOP OF THE INSULATOR. THE DAMASK COVER IS THEN PLACED OVER SPRING AND FOAM CORE. A MATCHING TOP IS THEN TAPED EDGED WITH

1 1/4" BINDING TAPE.

**COIL COUNT** QUEEN 345, FULL 299

**PACKAGING** THE FINISHED MATTRESS IS PLACED IN A

SEALED 2 MIL PLASTIC TO PREVENT SOILING.

MEETS 16 CFR 1632 AND 16 CFR 1633.

## **FOR PRODUCT INFORMATION & SALES**

**Hickory Springs Manufacturing** 

235 2nd Avenue NW | PO Box 128 • Hickory NC 28603-0128 | Telephone 828-328-2201