

6" Foam Hospitality Blue Sleeper Mattress

Hospitality Use



MATTRESS SPECIFICATIONS

SPRING	312 3/4 13 1/2 GAUGE BONNELL UNIT. HEAT TEMPERED FOR STRENGTH AND DURABILITY.
INSULATORS	ONE .75 OZ PAD PER SQUARE FOOT FIBER PAD IS STAPLED TO THE TOP, AND ONE .75 OZ PAD IS STAPLED TO THE BOTTOM OF THE SPRING UNIT.
QUILTING	A .3/8" POLYURETHANE FOAM TOPPER AND A .50 OZ RAYON/POLYESTER FLAME RETARDANT BARRIER IS MULTI-NEEDLE QUILTED TO THE DAMASK TICKING FOR COMFORT.
TOPPER	5/8" POLYURETHANE FOAM TOPPER FOR ADDITIONAL COMFORT.
FABRIC	45% POLYESTER, 55% POLYPROPYLENE DAMASK — FRENCH BLUE
BOTTOM	14 GAUGE COLOR COORDINATED STITCH BOND FILLER PANEL.
BINDING TAPE	A 1 1/4" POLYESTER BINDING TAPE IS SEWN TO TOP AND BOTTOM OF MATTRESS.
CONSTRUCTION	THE INSULATORS ARE STAPLED ON SPRING UNIT. A 5/8" POLYURETHANE FOAM TOPPER IS STAPLED TO THE INSULATOR. THE DAMASK COVER IS THEN PLACED OVER THE SPRING UNIT. A MATCHING TOP IS THEN TAPED EDGED WITH 1 1/4" BINDING TAPE.
COIL COUNT	QUEEN 345, FULL 299
PACKAGING	THE FINISHED MATTRESS IS PLACED IN A SEALED 2 MIL PLASTIC TO PREVENT SOILING.



- Manufactured in the USA
- Designed for traditional sleeper comfort
- 6" Innerspring mattress
- Available in Twin, Twin XL, Full and Queen
- Meets 16 CFR 1632 and 16 CFR 1633

Available Mattress Widths	
33" x 72" x 5.5"	Twin
36" x 72" x 5.5"	Twin XL
52" x 72" x 5.5"	Full
60" x 72" x 5.5"	Queen

FOR PRODUCT INFORMATION & SALES

Hickory Springs Manufacturing
 235 2nd Avenue NW | Hickory NC 28603-0128 | Telephone 828-328-2201

HICKORY SPRINGS

HOSPITALITY

www.hickorysprings.com