



HICKORY SPRINGS[®]
MANUFACTURING COMPANY

For additional information visit:
www.hickorysprings.com

Institutional Nylon Mattress

SPRING

THE 312 SPRING IS CONSTRUCTED OF HEAT TEMPERED HIGH CARBON STEEL AND FEATURES A FIVE TURN COIL. THE 13 GAUGE WIRE USED PROVIDES EXCELLENT SUPPORT AND FLEXING CAPABILITY. THE BORDER AND LACING HELICAL'S ARE MADE OF 17 GAUGE HIGH CARBON WIRE. THE ENTIRE SPRING HAS A 6 GAUGE BORDER WIRE RUNNING ON EDGE.

INSULATORS TOP

100 % POLYESTER 1.5 OZ PAD IS WRAPPED AROUND THE EDGES OF THE SPRING AND STAPLED TO THE TOP OF THE SPRING UNIT. THIS INSULATING MATERIAL IS FIRE RETARDANT AND IS CERTIFIED TO PASS THE 16 C.F.R. PART 1633.

INSULATORS BOTTOM

100 % POLYESTER 1.5 OZ PAD IS WRAPPED AROUND THE EDGES OF THE SPRING AND STAPLED TO THE BOTTOM OF THE SPRING UNIT. THIS INSULATING MATERIAL IS FIRE RETARDANT AND IS CERTIFIED TO PASS THE 16 C.F.R. PART 1633.

CORNER BLOCKS

4

STAPLES

110

TOPPER PAD

A 1" THICK LAYER OF HIGH DENSITY URETHANE FOAM IS STAPLED OVER THE INSULATOR PADDING ON THE TOP AND BOTTOM OF THE MATTRESS FOR EXTRA COMFORT AND SUPPORT.

MATTRESS TOP:

TICKING

210 DENIER NYLON COVER MEETS 2007 CPSC 16 CFR, PART 1633.

THREAD

FLAME RETARDANT THREAD

COVER

COVER HAS INVERTED SEAMS AND ZIPPERED ONE END

FIRE BARRIER BLEND.

FIRE BARRIER – FIBERGLASS / MODACRYLIC FABRIC

PACKAGING MIL

THE FINISHED MATTRESS IS PLACED IN A SEALED 2 PLASTIC



FOR PRODUCT INFORMATION & SALES

Hickory Springs Manufacturing

235 2ND Avenue NW | PO Box 128 • Hickory NC 28603-0128 | Telephone 828-328-2201

Blue Ridge Products

3050 Main Avenue NW | Hickory NC 28601 | Telephone 828-322-7990