



HICKORY SPRINGS[®]
MANUFACTURING COMPANY

For additional information visit:
www.hickorysprings.com

5.5" Beige Sofa Mattress



<u>SPRING</u>	253 3 ¾ 13 ½ GAUGE BONNELL UNIT. HEAT TEMPERED FOR STRENGTH AND DURABILITY.
<u>INSULATORS</u>	A .75 OZ POLYESTER INSULATOR IS STAPLED TO THE TOP AND BOTTOM OF THE SPRING.
<u>QUILTING</u>	A 1 OZ LAYER OF LOW MELT FIBER IS MULTI-NEEDLE QUILTED TO DAMASK TICKING FOR COMFORT. A .75 OZ POLYESTER FIBER IS QUILTED IN THE MATCHING BORDER.
<u>TOPPER</u>	A 1.25 OZ POLYESTER PAD IS STAPLED ON TOP OF INSULATOR.
<u>FABRIC</u>	45% POLYESTER, 55% POLYPROPYLENE DAMASK — BEIGE
<u>BOTTOM</u>	14 GAUGE COLOR COORDINATED STITCH BOND FILLER PANEL
<u>BINDING TAPE</u>	A 1 ¼" POLYESTER BINDING TAPE IS SEWN TO TOP AND BOTTOM OF MATTRESS.
<u>CONSTRUCTION</u>	THE INSULATORS ARE STAPLED ON SPRING UNIT. THE 1.25 POLYESTER PAD IS STAPLED ON TOP OF INSULATOR. THE DAMASK COVER IS THEN PLACED OVER THE SPRING UNIT. A MATCHING TOP IS THEN TAPED EDGED WITH 1 ¼" BINDING TAPE.
<u>COIL COUNT</u>	QUEEN 299, FULL 253
<u>PACKAGING</u>	THE FINISHED MATTRESS IS PLACED IN A SEALED 2 MIL PLASTIC TO PREVENT SOILING.



FOR PRODUCT INFORMATION & SALES

Hickory Springs Manufacturing

235 2ND Avenue NW | PO Box 128 • Hickory NC 28603-0128 | Telephone 828-328-2201

Blue Ridge Products

3050 Main Avenue NW | Hickory NC 28601 | Telephone 828-322-7990

MEETS 16 CFR 1632 AND 16 CFR 1633.