6" Hybrid Hospitality

Sleeper Mattress



MATTRESS SPECIFICATIONS

SPRING

312 3 ¾ 13 ½ GAUGE BONNELL UNIT. HEAT TEMPERED FOR STRENGTH AND

DURABILITY.

INSULATORS

A .75 OZ POLYESTER INSULATOR IS STAPLED TO THE TOP AND BOTTOM OF

THE SPRING.

QUILTING

A 1 OZ LAYER OF LOW MELT FIBER IS MULTI-NEEDLE QUILTED TO DAMASK TICKING FOR COMFORT. A .75 OZ POLYESTER FIBER IS QUILTED IN THE

MATCHING BORDER.

TOPPER

A 1.25" VISCO GEL TOPPER FOR

ADDITIONAL COMFORT

FABRIC

45% POLYESTER, 55% POLYPROPYLENE

DAMASK - WHITE

BOTTOM

14 GAUGE COLOR COORDINATED STITCH

BOND FILLER PANEL

BINDING TAPE

A 1 ¼" POLYESTER BINDING TAPE IS SEWN TO TOP AND BOTTOM OF MATTRESS.

CONSTRUCTION

THE INSULATORS ARE STAPLED ON TOP AND BOTTOM OF SPRING UNIT. THE 1.25 VISCO GEL PAD IS APPLIED ON TOP OF INSULATOR. THE DAMASK COVER IS THEN PLACED OVER THE SPRING UNIT. A MATCHING TOP IS THEN TAPED EDGED

WITH 1 1/4" BINDING TAPE.

COIL COUNT

QUEEN 345, FULL 299

PACKAGING

THE FINISHED MATTRESS IS PLACED IN A SEALED 2 MIL PLASTIC TO PREVENT

SOILING.

MEETS 16 CFR 1632 AND 16 CFR 1633.



- · Manufactured in the USA
- · Designed for traditional sleeper comfort
- · 6" innerspring mattress
- · Available in Twin, Twin XL, Full and Queen

33" x 72" x 6"	Twin
36" x 72" x 6"	Twin XL
52" x 72" x 6"	Full
60" x 72" x 6"	Queen

FOR PRODUCT INFORMATION & SALES

Hickory Springs Manufacturing 235 2nd Avenue NW | Hickory NC 28603-0128 | Telephone 828-328-2201

HICKORY SPRINGS

- HOSPITALITY -

www.hickorysprings.com